

ZENKU

Wall Panel technical specifications

COVER Collection

GENERAL CHARACTERISTICS

Cover is a decorative product for walls and ceilings, composed by a high quality moisture resistant HDF and a decorative coating.

It is installed on the wall on battens and fixed to it with staples or needles. Do not use glues, silicones or the like under any circumstances, as they can cause peeling or surface stains.

CHARACTERISTICS OF THE BASE BOARD

CHARACTERISTICS	NORM	VALUE
Board Type		High Density Fibreboard Moisture resistant HDF
Approximate average density	EN 323	900 Kg/m ³
24h swelling	EN 317	≤12%
HDF formaldehyde content	EN ISO 12460-5	E1
Nominal Thickness	EN ISO 12460-5	8 mm

COATING CHARACTERISTICS: DECORATIVE COATING

Surface resistance cold liquids:

TESTS	NORM	VALUE
Liquid Surface Resistance	UNE EN 12720 (10 min)	Acético 5% ≥ 3 Alcohol 96% ≥ 3 Oil ≥ 3
PEFC Certification		PEFC-COC-0332

DIMENSIONS

Length: 2700 mm Length: 2700 mm
Width: 214 mm Width: 325 mm

MAINTENANCE

This product is not suitable for outdoor use. Do not apply on walls or environments with excessive humidity.

The cleaning of the product must be done dry or with a cloth slightly moistened with water.

Do not use aggressive chemical products that contain alcohol, acetone, ammonia, which can cause significant degradation of the surface.

Avoid contact with oily products as it can cause stains on the decoration.

Do not expose to temperatures above 50°C (such as radiators, stoves, light bulbs, etc.).